

PROFESSIONAL KITCHENS

600 DEPTH COUNTERS

Model: KTP6D/02

Code: 04201407

K-ONE

325x430

REFRIGERATED COUNTER - Refrigerated counter 600
depth
2 doors
stainless steel normal work top

- made in stainless steel
- 325x430 mm racks capacity
- ventilated cooling system
- 2.8" touch control panel, digital display
- technical panel at right side
- automatic defrosting system with heating elements
- automatic elimination of condensate water
- automatic defrosting system with heating elements
- optional equipment: drawer unit with 2 1/2 drawers
- supply with: 1 325x430mm shelf each door



TECHNICAL DATA

Body Height	mm	665
Insulation thickness	mm	50
Capacity (net)	l	147
Capacity (gross)	l	220
Doors	nr	2
External dimensions (WxDxH)	mm	1300 x 600 x 850
Trays/Shelves capacity		325x430 mm
Rack positions	mm	7
Stainless steel top thickness	mm	10/10 H 40
Top type		normal work top
Condensing unit		plug-in
Evaporators	nr	1
Temperature	°C	-2/+8°C
Gas		R290
Max abs. power	W	225*
Cooling power	W	406*
Input voltage		1x230V/50Hz
Energy efficiency class		B
Energy consumption	kWh/24h	1,69
Energy consumption	kWh/year	618
Energy efficiency index		28,6
Climate class		5
Packaging dimensions (WxDxH)	mm	137 x 76 x 112
Volume (gross)	mc	1,17
Net weight	kg	81
Gross weight	kg	96

ACCESSORIES:



Refrigerated drawer unit with 2 1/2 drawers (overprice)

04201300



Pair of runners for 600 depth counter

40200504



32,5X43 cm rilsan shelf (for 600 depth counter)

40200502



Set of nr. 4 Ø 125 castors (2 self-locking)

40200530



Wi-Fi supervising system (overprice)

45000565



60Hz frequency

45000560

INSTALLATION DIAGRAM:

PART. INGOMBRO PORTE

GAS REFRIGERANTE R290
POTENZA MAX ASSORBITA (TN) :225 W
POTENZA MAX ASSORBITA (BT) :485 W
ALIMENTAZIONE : 230 V ~ 1 - 50Hz (* spina SHUKO) - Lunghezza cavo 2 mt

DESCRIZIONE	SCHEMA INSTALLAZIONE	CODICE	NOTE
	KTP-KTN 6D / 02 R290 NEW		
DATA	SCALA	DIS.	NOME FILE
04.09.2025	1:20	MARCO P.	
- AI TERMINI DI LEGGE QUESTO DISEGNO E' DI PROPRIETA' DI GEMM srl E NON PUO' ESSERE USATO O RIPRODOTTO SENZA NOSTRA AUTORIZZAZIONE -			