

PASTRY

800 DEPTH COUNTERS

Model: KTP8/02S

Code: 04230010

K-ONE

600X400


EN REFRIGERATED COUNTER - Refrigerated pastry counter suitable for 600x400 trays

2 doors

without work top

- made in stainless steel
- 600x400 trays capacity
- refrigeration system HSS "Helped Static System"
- 2.8" touch control panel, digital display
- technical panel at right side
- automatic defrosting system with heating elements
- automatic elimination of condensate water
- automatic defrosting system with heating elements
- supply with: 7 pair of runners each door












TECHNICAL DATA

Body Height	mm	710
Insulation thickness	mm	50
Capacity (net)	l	270
Capacity (gross)	l	390
Doors	nr	2
External dimensions (WxDxH)	mm	1540 x 770 x 860
Trays/Shelves capacity		600x400 mm
Rack positions	mm	7
Top type		without work top
Condensing unit		plug-in
Evaporators	nr	1
Temperature	°C	0/+8°C
Gas		R290
Max abs. power	W	260*
Cooling power	W	410*
Input voltage		1x230V/50Hz
Energy efficiency class		B
Energy consumption	kWh/24h	1,91
Energy consumption	kWh/year	695
Energy efficiency index		28,1
Climate class		5
Packaging dimensions (WxDxH)	mm	170 x 96 x 110
Volume (gross)	mc	1,8
Net weight	kg	123
Gross weight	kg	138

ACCESSORIES:

	Rilsan 60x40 cm shelf	45020550
	Pair of runners for 60x40 cm trays	20808031
	Stainless steel cm 40x60x2h tray	42000560
	Stainless steel cm 40x60x3h tray	42000562
	Set of nr. 4 Ø 125 castors (2 self-locking)	40200530
	Wi-Fi supervising system (overprice)	45000565
	60Hz frequency	45000560

INSTALLATION DIAGRAM:

GAS REFRIGERANTE R290
POTENZA MAX ASSORBITA (TN) : 260 W
POTENZA MAX ASSORBITA (BT) : 490 W
ALIMENTAZIONE : 230 V ~ 1 - 50Hz (* spina SHUKO) - Lunghezza cavo 2 mt

PART. INGOMBRO PORTE

DESCRIZIONE		CODICE	
KONE®		705045900	
SCHEMA INSTALLAZIONE		NOME FILE	
KTP-KTN 8 / 02 R290 NEW		MARCO P.	
DATA	SCALA	DIS.	SCALE
05.09.2025	1:20	MARCO P.	1:20

NOTE

- AI TERMINI DI LEGGE QUESTO DISEGNO E' DI PROPRIETA' DI GEMM srl E NON PUO' ESSERE USATO O RIPRODOTTO SENZA NOSTRA AUTORIZZAZIONE -