

PASTRY

800 DEPTH COUNTERS

Model: KTN8/03A

Code: 04240022

K-ONE

600X400

EN FREEZER COUNTER - Freezer pastry counter suitable for 600x400 trays

3 doors

stainless steel work top with backsplash







- made in stainless steel
- 600x400 trays capacity
- refrigeration system HSS "Helped Static System"
- 2.8" touch control panel, digital display
- technical panel at right side
- automatic defrosting system with heating elements
- automatic elimination of condensate water
- automatic defrosting system with heating elements
- supply with: 7 pair of runners each door



TECHNICAL DATA

Body Height	mm	710
Insulation thickness	mm	50
Capacity (net)	l	404
Capacity (gross)	l	605
Doors	nr	3
External dimensions (WxDxH)	mm	2100 x 800 x 1000
Trays/Shelves capacity		600x400 mm
Rack positions	mm	7
Stainless steel top thickness	mm	15/10 H 40
Top type		work top with back spalsh
Condensing unit		plug-in
Evaporators	nr	2
Temperature	°C	-15/-20°C
Gas		R290
Max abs. power	W	930*
Cooling power	W	930**
Input voltage		1x230V/50Hz
Energy efficiency class		D
Energy consumption	kWh/24h	8,7
Energy consumption	kWh/year	3171
Energy efficiency index		66,9
Climate class		5
Packaging dimensions (WxDxH)	mm	225 x 96 x 110
Volume (gross)	mc	2,38
Net weight	kg	170
Gross weight	kg	185

ACCESSORIES:

	Rilsan 60x40 cm shelf	45020550
	Pair of runners for 60x40 cm trays	20808031
	Stainless steel cm 40x60x2h tray	42000560
	Stainless steel cm 40x60x3h tray	42000562
	Set of nr. 6 Ø 125 castors (2 self-locking)	40200532
	Wi-Fi supervising system (overprice)	45000565
	60Hz frequency	45000560

INSTALLATION DIAGRAM:

GAS REFRIGERANTE R290
POTENZA MAX ASSORBITA (TN) : 260 W
POTENZA MAX ASSORBITA (BT) : 930 W
ALIMENTAZIONE : 230 V ~ 1 - 50Hz (* spina SHUKO) - Lunghezza cavo 2 m

DESCRIZIONE		CODICE	
KONE® SCHEMA INSTALLAZIONE KTP-KTN 8 / 03 R290 NEW		705046000	
DATA	SCALA	DIS.	NOME FILE
05.09.2025	1:20	MARCO P.	

NOTE
 - AI TERMINI DI LEGGE QUESTO DISEGNO E' DI PROPRIETA' DI GEMM srl E NON PUO' ESSERE USATO O RIPRODOTTO SENZA NOSTRA AUTORIZZAZIONE -