

PROFESSIONAL KITCHENS

CABINETS FOR PROFESSIONAL KITCHENS

Model: KXP/70

Code: 04500260


K-ONE

700 liters

GN 2/1 POSITIVE DEEP-DRAWN INTERNAL SIDES CABINET, "A" ENERGY CLASS - Refrigerated upright cabinet with deep-drawn internal sides for GN 2/1 racks, 55 mm pitch for 24 positions and complete with door lock with key and led light. Prearranged for remote condensing unit with valve system on request.

- made in stainless steel
- GN 2/1 racks capacity
- ventilated cooling system
- 2.2" touch control panel, digital display
- technical compartment: placed on the top
- automatic defrosting system with hot gas
- automatic elimination of condensate water
- automatic defrosting system with hot gas
- supply with: 3 GN 2/1 shelves











TECHNICAL DATA

Insulation thickness	mm	95
Capacity (net)	l	435
Capacity (gross)	l	558
Doors	nr	1
External dimensions (WxDxH)	mm	720 x 910 x 2090
Trays/Shelves capacity		GN 2/1
Rack positions	mm	24
Condensing unit		plug-in
Evaporators	nr	1
Temperature	°C	-2/+8°C
Gas		R600a
Max abs. power	W	185*
Cooling power	W	370*
Input voltage		1x230V/50Hz
Energy efficiency class		A
Energy consumption	kWh/24h	0,89
Energy consumption	kWh/year	325
Energy efficiency index		0,89
Climate class		5
Packaging dimensions (WxDxH)	mm	83 x 97 x 221
Volume (gross)	mc	1,78
Net weight	kg	146
Gross weight	kg	156

ACCESSORIES:

	Pair of runners for GN 2/1 shelf	45001550
	GN 2/1 rilsan shelf	45000500
	Stainless steel GN 2/1 shelf	45000515
	Prearranged version with valve system for POSITIVE cabinet (deduction)	K01P-REMOTE
	Wi-Fi supervising system (overprice)	45000565
	60Hz frequency	45000560

INSTALLATION DIAGRAM:

