

PROFESSIONAL KITCHENS

CABINETS FOR PROFESSIONAL KITCHENS

Model: KGPV/01

Code: 04501885

K-ONE

700 liters


GN 2/1 POSITIVE UPRIGHT CABINET WITH GLASS DOOR

- Refrigerated upright cabinet glass door for GN 2/1 racks.

Prearranged for remote condensing unit with valve system on request.

- made in stainless steel
- GN 2/1 racks capacity
- ventilated cooling system
- 2.8" touch control panel, digital display
- technical compartment: placed on the top
- automatic defrosting system with heating elements
- automatic elimination of condensate water
- automatic defrosting system with heating elements
- Supply with: 3 GN 2/1 shelves













TECHNICAL DATA

Doors	nr	1
Trays/Shelves capacity		GN 2/1
Capacity (net)	l	404
Capacity (gross)	l	585
External dimensions (WxDxH)	mm	720 x 800 x 2090
Insulation thickness	mm	60
Evaporators	nr	1
Temperature	°C	+2/+10°C
Condensing unit		plug-in
Max abs. power	W	185*
Cooling power	W	425*
Gas		R290
Input voltage		1x230V/50Hz
Energy efficiency class		D
Energy consumption	kWh/24h	2,08
Energy consumption	kWh/year	760
Energy efficiency index		59,74
Climate class		4
Packaging dimensions (WxDxH)	mm	87 x 77 x 224
Volume (gross)	mc	1,5
Net weight	kg	111
Gross weight	kg	121

*Evap. -10°C, Cond. +45°C

ACCESSORIES:

	Pair of runners for GN 2/1 shelf	45001550
	GN 2/1 shelf	45000500
	GN 2/1 stainless steel shelf	45000515
	Pedal for single door (overprice)	45000530
	Set of 4 Ø 100 castors (overprice)	45000540
	Prearranged version with valve system for normal temperature equipment (deduction)	K01P-REMOTE
	Wi-Fi supervising system (overprice)	45000565
	60Hz frequency	45000560