

PROFESSIONAL KITCHENS

CABINETS FOR PROFESSIONAL KITCHENS

Model: KGP/02

Code: 04501890


K-ONE

1400 liters

GN 2/1 POSITIVE UPRIGHT CABINET - Refrigerated upright cabinet for GN 2/1 racks. Prearranged for remote condensing unit with valve system on request.

- made in stainless steel
- GN 2/1 racks capacity
- ventilated cooling system
- 2.8" touch control panel, digital display
- technical compartment: placed on the top
- automatic defrosting system with heating elements
- automatic elimination of condensate water
- automatic defrosting system with heating elements
- supply with: 6 GN 2/1 shelves













TECHNICAL DATA

Insulation thickness	mm	60
Capacity (net)	l	808
Capacity (gross)	l	1287
Doors	nr	2
External dimensions (WxDxH)	mm	1440 x 810 x 2090
Trays/Shelves capacity		GN 2/1
Rack positions	mm	19
Condensing unit		plug-in
Evaporators	nr	1
Temperature	°C	-2/+8°C
Gas		R290
Max abs. power	W	270*
Cooling power	W	560*
Input voltage		1x230V/50Hz
Energy efficiency class		D
Energy consumption	kWh/24h	2,91
Energy consumption	kWh/year	1060
Energy efficiency index		54,76
Climate class		5
Packaging dimensions (WxDxH)	mm	148 x 96 x 224
Volume (gross)	mc	3,18
Net weight	kg	176
Gross weight	kg	186

ACCESSORIES:

	Pair of runners for GN 2/1 shelf	45001550
	GN 2/1 rilsan shelf	45000500
	Stainless steel GN 2/1 shelf	45000515
	Pedal for double door	45000532
	Set of Ø 100 castors	45000540
	Prearranged version with valve system for POSITIVE cabinet (deduction)	K01P-REMOTE
	Wi-Fi supervising system (overprice)	45000565
	60Hz frequency	45000560

INSTALLATION DIAGRAM:

