

PASTRY|PIZZERIA

PASTRY CABINETS

Model: KPP/20

Code: 04510500


K-ONE

20 TRAYS 600x400

PASTRY POSITIVE UPRIGHT CABINET 20 TRAYS - Pastry refrigerated cabinet for 20 600x400 trays, with high umidity level for a better storage of fresh product and energy save. Available also prearranged for remote condensing unit with valve system.

- made in staineless steel
- 600x400 trays capacity
- cooling system with indirect/soft ventilation
- 2.8" touch control panel, digital display
- technical compartment: placed on the top
- automatic defrosting system with hot gas
- automatic elimination of condensate water
- automatic defrosting system with hot gas
- supply with: 20 pair of runners for 600x400mm trays
- not included: trays/shelves















TECHNICAL DATA

Insulation thickness	mm	75
Capacity (net)	l	304
Capacity (gross)	l	500
Doors	nr	1
External dimensions (WxDxH)	mm	790 x 690 x 2140
Trays/Shelves capacity		600x400 mm
Rack positions	mm	74
Condensing unit		plug-in
Evaporators	nr	1
Temperature	°C	-2/+8°C
Gas		R290
Max abs. power	W	500*
Cooling power	W	605*
Input voltage		1x230V/50Hz
Energy efficiency class		D
Energy consumption	kWh/24h	2,25
Energy consumption	kWh/year	820
Energy efficiency index		73,9
Climate class		5
Packaging dimensions (WxDxH)	mm	87 x 77 x 226
Volume (gross)	mc	1,51
Net weight	kg	125
Gross weight	kg	135

ACCESSORIES:

	Pair of runners for 60x40 cm tray/shelf	45020503
	Rilsan 60x40 cm shelf	45020550
	60x40 cm stainless steel shelf	45100242
	Stainless steel cm 40x60x2h tray	42000560
	Stainless steel cm 40x60x3h tray	42000562
	Toughened glass door with internal LED light (overprice)	45020525
	Set of Ø 100 castors	45000540
	Prearranged version with valve system for POSITIVE cabinet (deduction)	K01P-REMOTE
	Wi-Fi supervising system (overprice)	45000565
	60Hz frequency	45000560

INSTALLATION DIAGRAM:

FRONT VIEW DIMENSIONS:
 Total height: 2140
 Main body height: 1990
 Top panel width: 790
 Main body width: 550
 Side panel width: 120 (each side)
 Bottom feet height: 150

SIDE VIEW DIMENSIONS:
 Total depth: 682
 Main body depth: 610
 Side panel depth: 72
 Main body width: 455
 Side panel width: 143
 Bottom feet height: 86

REAR VIEW DIMENSION:
 Total depth: 1396

GAS REFRIGERANTE R290
 ALIMENTAZIONE ELETTRICA: 230V 50HZ (*spina SCHUKO)
 Lunghezza cavo 3mt
 POTENZA ELETTRICA MAX ASSORBITA (TN) : 500 W
 POTENZA ELETTRICA MAX ASSORBITA (BT) : 795 W
 POTENZA REFRIGERANTE TN (-10°C+45°C): 605 W
 POTENZA REFRIGERANTE BT (-23,3°C+54,4°C): 650 W

DESCRIZIONE	SCHEMA INSTALLAZIONE	CODICE	NOTE
KPP-KPN 20 R290 NEW		705045500	
DATA	SCALA	DIS.	MARCO P.
05.09.2025	1:20		
- AI TERMINI DI LEGGE QUESTO DISEGNO E' DI PROPRIETA' DI GEMM srl E NON PUO' ESSERE USATO O RIPRODOTTO SENZA NOSTRA AUTORIZZAZIONE -			