

## ICE CREAM|PASTRY|PROFESSIONAL KITCHENS

**BLAST CHILLERS/SHOCK FREEZERS FOR TROLLEYS**

**Model: KCC/4008**

**Code: 04611420**


K-ONE

*1 GN 2/1 // 600x800 TROLLEY*

BLAST CHILLER / SHOCK FREEZER FOR 1 GN 2/1 - 600X800 TROLLEY - The K-ONE range of blast chillers / shock freezers for trolleys is designed to meet the rapid chilling needs of medium- to large-scale laboratories, from catering facilities to semi-industrial pastry and bakery labs. Chilling from +90°C to +3°C in 90 minutes and freezing from +90°C to -18°C in 240 minutes, with a minimum air temperature of -40 °C. 7" touchscreen control panel with remote Wi-Fi supervision via Cloud. Core probe and USB port come as standard.





- made in stainless steel
- GN 2/1 or 600x800 trolley capacity
- chilling from +90°C to +3°C in 90 minutes and freezing from +90°C to -18°C in 240 minutes, reaching minimum air temperature -40°C
- 7" color touch-screen graphic display
- technical compartment: placed on the top
- automatic defrosting system with hot gas
- condensation drain pipe (prearrange water drain)
- automatic defrosting system with hot gas
- supply with: USB port, Cloud Wi-Fi supervising system
- not included: trolley



## TECHNICAL DATA

Insulation thickness	mm	70
Doors	nr	1
External dimensions (WxDxH)	mm	890 x 1320 x 2420
Internal dimensions (WxDxH)	mm	710 x 860 x 1870
Condensing unit		plug-in
Evaporators	nr	1
Trolleys capacity	nr	1 600x800
Yield* chilling / freezing	kg	+90/+3°C = 95kg // +90/-18°C = 75kg
Gas		R452A
		+90/+3°C = 95kg // +90/-18°C = 75kg
Max abs. power	W	4999*
Cooling power	W	3980**
Input voltage		3x400V/50Hz
Compressor power	Hp	3,5
Climate class		5
Packaging dimensions (WxDxH)	mm	100 x 155 x 256
Volume (gross)	mc	3,97
Net weight	kg	477
Gross weight	kg	522

## ACCESSORIES:

o	Ozone sterilizer kit for KCC/4008-4011-4014 (overprice)	45100912
	110 cm long stainless steel ramp KCC/4008-4011-4014 (overprice)	45100961
	60Hz frequency	45000560

## INSTALLATION DIAGRAM:

**CELLA PREDISPOSTA PER GAS R290**

(R) ALIMENTAZIONE ELETTRICA : 400V 3F+N 50Hz  
 POTENZA ELETTRICA ASSORBITA : max 2.000W  
 CAVO DI ALIMENTAZIONE 5mt  
 POTENZA REFRIGERANTE (-23°C / +54°C): 5.622W

(S) ATTENZIONE!!! PREDISPORRE LO SCARICO DI CONDENSA

DESCRIZIONE		SCHEMA INSTALLAZIONE KCC - 4008 R290 NEW	
DATA	19.09.2025	SCALA	1:20
DIS.		MARCO P.	
CODICE		705046900	
NOME FILE		-	
NOTE			
- AI TERMINI DI LEGGE QUESTO DISEGNO E' DI PROPRIETA' DI GEIMM srl E NON PUO' ESSERE USATO O RIPRODOTTO SENZA NOSTRA AUTORIZZAZIONE -			