

ICE CREAM|PASTRY|PROFESSIONAL KITCHENS

BLAST CHILLERS/SHOCK FREEZERS FOR TROLLEYS

Model: KCC/4014

Code: 04611620


K-ONE

1 GN 2/1 // 600x800 TROLLEY

BLAST CHILLER / SHOCK FREEZER FOR 1 GN 2/1 - 600X800 TROLLEY - The K-ONE range of blast chillers / shock freezers for trolleys is designed to meet the rapid chilling needs of medium- to large-scale laboratories, from catering facilities to semi-industrial pastry and bakery labs. Chilling from +90°C to +3°C in 90 minutes and freezing from +90°C to -18°C in 240 minutes, with a minimum air temperature of -40 °C. 7" touchscreen control panel with remote Wi-Fi supervision via Cloud. Core probe and USB port come as standard.




- made in stainless steel
- GN 2/1 or 600x800 trolley capacity
- chilling from +90°C to +3°C in 90 minutes and freezing from +90°C to -18°C in 240 minutes, reaching minimum air temperature -40°C
- 7" color touch-screen graphic display
- technical compartment: placed on the top
- automatic defrosting system with hot gas
- condensation drain pipe (prearrange water drain)
- automatic defrosting system with hot gas
- supply with: USB port, Cloud Wi-Fi supervising system
- not included: trolley



TECHNICAL DATA

Insulation thickness	mm	70
Doors	nr	1
External dimensions (WxDxH)	mm	1360 x 1340 x 2420
Internal dimensions (WxDxH)	mm	710 x 960 x 2010
Condensing unit		remote condensing unit (connection pipes not included)
Evaporators	nr	1
Trolleys capacity	nr	1 600x800
Yield* chilling / freezing	kg	+90/+3°C = 150kg // +90/-18°C = 130kg +90/+3°C = 150kg // +90/-18°C = 130kg
Max abs. power	W	805 / 8400*
Cooling power	W	7300**
Input voltage		3x400V/50Hz
Compressor power	Hp	6
Climate class		5
Volume (gross)	mc	8,79
Net weight	kg	917
Gross weight	kg	967

ACCESSORIES:



Additional pass-through door for KCC/4014 (overprice)

45100951



Ozone sterilizer kit for KCC/4008-4011-4014 (overprice)

45100912



110 cm long stainless steel ramp KCC/4008-4011-4014 (overprice)

45100961



Low noise housing condensing unit for KCC/4041 (overprice)

45100943



60Hz frequency

45000560

INSTALLATION DIAGRAM:

