

PROFESSIONAL KITCHENS

TAVOLI PROFONDITA' 600

Modello: KTP6D/04A Codice: 04201462

K-ONE

325x430

TAVOLO REFRIGERATO - Tavolo refrigerato gastronomia
con profondità 600

4 porte

piano di lavoro inox con alzatina posteriore

- costruzione in acciaio inox
- capacità: griglie 325x430 mm
- refrigerazione ventilata
- pannello di controllo touch 2.8", visualizzazione digit
- vano tecnico a dx
- sbrinamento automatico con resistenze elettriche
- eliminazione automatica acqua di condensa
- allestimenti a richiesta: cassettera a 2 cassetti 1/2
- dotazione: 1 griglia 325x430 mm per porta



DATI TECNICI

Altezza corpo	mm	665
Isolamento	mm	50
Capacità (netta)	l	293
Capacità (lorda)	l	466
Porte	nr	4
Misure esterne (WxDxH)	mm	2220 x 600 x 950
Capacità teglie		325x430 mm
Posizioni su cremagliera	nr	7
Spessore piano	mm	10/10 H 40
Tipologia piano		con alzatina posteriore
Motore		a bordo
Evaporatori	nr	2
Temperatura	°C	-2/+8°C
Gas		R290
Potenza max assorbita	W	440*
Potenza refrigerante	W	605*
Tensione Alimentazione		1x230V/50Hz
Classe energetica		B
Consumo energetico	kWh/24h	2,46
Consumo energetico	kWh/annum	900
Indice efficienza energetica		35,4
Classe climatica		5
Misure imballo (WxDxH)	mm	230 x 76 x 112
Volume imballo lordo	mc	1,96
Peso netto	kg	155
Peso lordo	kg	170

ACCESSORI



Refrigerated drawer unit with 2 1/2 drawers (overprice)

04201300



Pair of runners for 600 depth counter

40200504



32,5X43 cm rilsan shelf (for 600 depth counter)

40200502

Set of nr. 6 Ø 125 castors (2 self-locking)

40200532



Wi-Fi supervising system (overprice)

45000565



60Hz frequency

45000560

SCHEMA DI INSTALLAZIONE

Technical drawing showing front and side views of the KONE KTP6D/04 R290 NEW unit. Dimensions are provided in millimeters.

Front View Dimensions:
 Total width: 2220 mm
 Total height: 2210 mm
 Top panel width: 850 mm
 Top panel height: 100 mm
 Middle panel height: 665 mm
 Bottom panel height: 145 mm
 Bottom panel width: 74 mm
 Total depth: 1210 mm
 Distance from wall to top panel: 250 mm
 Distance from wall to middle panel: 74 mm
 Distance from wall to bottom panel: 350 mm
 Distance from wall to top of unit: 1860 mm
 Distance from wall to bottom of unit: 856 mm
 Distance from wall to top of door: 70 mm

Side View Dimensions:
 Total height: 600 mm
 Total width: 950 mm
 Top panel height: 15 mm
 Middle panel height: 565 mm
 Middle panel width: 810 mm
 Bottom panel height: 3 mm
 Distance from wall to top of unit: 40 mm
 Distance from wall to middle of unit: 70 mm
 Distance from wall to bottom of unit: 130 mm
 Distance from wall to top of door: 390 mm
 Distance from wall to middle of door: 530 mm
 Distance from wall to bottom of door: 60 mm
 Total depth: 590 mm

PART. INGOMBRO PORTE

Technical drawing showing the door opening dimensions. Dimensions are provided in millimeters.

Door Opening Dimensions:
 Total width: 1010 mm
 Total height: 2210 mm
 Distance from wall to top of door: 530 mm
 Distance from wall to middle of door: 480 mm

⚡

GAS REFRIGERANTE R290
 POTENZA MAX ASSORBITA (TN) : 445 W
 POTENZA MAX ASSORBITA (BT) : 797 W
 ALIMENTAZIONE : 230 V ~ 1 - 50Hz (* spina SHUKO) - Lunghezza cavo 2 mt

DESCRIZIONE	SCHEMA INSTALLAZIONE	CODICE	NOTE
KTP-KTN 6D / 04 R290 NEW		705044600	
DATA	SCALA	DIS.	NOME FILE
04.09.2025	1:20	MARCO P.	
- AI TERMINI DI LEGGE QUESTO DISEGNO E' DI PROPRIETA' DI GEMM srl E NON PUO' ESSERE USATO O RIPRODOTTO SENZA NOSTRA AUTORIZZAZIONE -			