

PROFESSIONAL KITCHENS

TAVOLI PROFONDITA' 700

Modello: KTHP7D/03 Codice: 04330102

K-ONE

GN 1/1

TAVOLO REFRIGERATO GN 1/1 CORPO H 760 VANO
TECNICO A DX - Tavolo refrigerato gastronomia con
profondità 700
3 porte
piano di lavoro inox liscio

- costruzione in acciaio inox
- capacità: griglie GN 1/1
- refrigerazione ventilata
- pannello di controllo touch 2.8", visualizzazione digit
- vano tecnico a dx
- sbrinamento automatico con resistenze elettriche
- eliminazione automatica acqua di condensa
- allestimenti a richiesta: cassettiera a 2 cassetti 1/2 oppure a 3 cassetti 1/3
- dotazione: 2 griglie GN 1/1 per porta



DATI TECNICI

Altezza corpo	mm	760
Isolamento	mm	50
Capacità (netta)	l	320
Capacità (lorda)	l	485
Porte	nr	3
Misure esterne (WxDxH)	mm	1760 x 700 x 900
Capacità teglie		GN 1/1
Posizioni su cremagliera	nr	8
Spessore piano	mm	10/10 H 40
Tipologia piano		liscio
Motore		a bordo
Evaporatori	nr	1
Temperatura	°C	-2/+8°C
Gas		R290
Potenza max assorbita	W	225*
Potenza refrigerante	W	406*
Tensione Alimentazione		1x230V/50Hz
Classe energetica		A
Consumo energetico	kWh/24h	1,78
Consumo energetico	kWh/annum	650
Indice efficienza energetica		24,9
Classe climatica		5
Misure imballo (WxDxH)	mm	185 x 76 x 112
Volume imballo lordo	mc	1,57
Peso netto	kg	143
Peso lordo	kg	158

ACCESSORI



Refrigerated drawer unit with 2 1/2 drawers (overprice)

04331200



Refrigerated drawer unit with 3 1/3 drawers (overprice)

04331205



Pair of runners for GN 1/1 shelf

40200506



GN 1/1 rilsan shelf

40200500



GN 1/1 stainless steel shelf

45100240



Set of nr. 4 Ø 125 castors (2 self-locking)

40200530



Wi-Fi supervising system (overprice)

45000565



60Hz frequency

45000560

SCHEMA DI INSTALLAZIONE

FRONT VIEW DIMENSIONS:
 Total width: 1000 mm
 Internal width: 860 mm
 Total height: 700 mm
 Internal height: 685 mm
 Top panel thickness: 15 mm
 Bottom panel thickness: 3 mm
 Distance from wall to bottom panel: 40 mm
 Distance from wall to top panel: 70 mm
 Distance from wall to bottom panel (internal): 490 mm
 Distance from wall to top panel (internal): 630 mm
 Total distance from wall to bottom panel: 690 mm
 Total distance from wall to top panel: 130 mm
 Distance between panels: 60 mm

SIDE VIEW DIMENSIONS:
 Total height: 1760 mm
 Top panel height: 100 mm
 Middle panel height: 40 mm
 Bottom panel height: 100 mm
 Total width: 900 mm
 Internal width: 760 mm
 Distance from wall to top panel: 5 mm
 Distance from wall to middle panel: 250 mm
 Distance from wall to bottom panel: 74 mm
 Distance from wall to top panel (internal): 1606 mm
 Distance from wall to middle panel (internal): 1400 mm
 Distance from wall to bottom panel (internal): 350 mm
 Total distance from wall to top panel: 1750 mm

PART. INGOMBRO PORTE

DOOR OPENING DIMENSIONS:
 Total width: 1750 mm
 Distance from wall to door edge: 630 mm
 Distance between door edges: 480 mm
 Total distance from wall to door edge: 1110 mm

⚡
GAS REFRIGERANTE R290
POTENZA MAX ASSORBITA (TN) : 225 W
POTENZA MAX ASSORBITA (BT) : 756 W
ALIMENTAZIONE : 230 V ~ 1 - 50Hz (* spina SHUKO) - Lunghezza cavo 2 mt

DESCRIZIONE	SCHEMA INSTALLAZIONE	CODICE	705045300
	KTHP-KTHN 7D / 03 R290 NEW		NOME FILE
DATA	SCALA	DIS.	MARCO P.
04.09.2025	1:20		
- AI TERMINI DI LEGGE QUESTO DISEGNO E' DI PROPRIETA' DI GEMM srl E NON PUO' ESSERE USATO O RIPRODOTTO SENZA NOSTRA AUTORIZZAZIONE -			