PROFESSIONAL KITCHENS

CABINETS FOR PROFESSIONAL KITCHENS **Model: XFB/71** **Code: 45002130**

SPACE PLUS

GN 2/1 NEGATIVE UPRIGHT CABINET WITH 2 HALF DOORS - Freezer upright cabinet for GN 2/1 racks, complete with door lock with key and led light. Prearranged for remote condensing unit with valve system on request.



- Construction: made in stainelss steel
- Deep-drawn internal sides
- Internal capacity: GN 2/1 racks
- Position of technical compartment: on top
- Refrigeration type: ventilated cooling system
- Control board panel: 2.8" touch control panel, digital display
- Prearranged to be installed on plinth
- Defrosting system: automatic with hot gas
- Evaporation of condensation water: automatic
- Optional equipment: prearranged for remote system (R452A gas valve)
- Supply with: 4 GN 2/1 shelves

GEMM®



Technical Data:


Doors	nr	2 1/2
Capacity (net)	l	433
Capacity (gross)	l	556
External dimensions (WxDxH)	cm	70 x 89 x 209
Insulation thickness	mm	80
Tray pitch	mm	55
Rack positions	nr	24
Standard lock		YES
Standard light		YES
Temperature	°C	-18/-21°C
Condensing unit		plug-in unit
Compressor power	Hp	1/2
Gas		R290
Ventilation control		NO
Humidity control		NO
Max abs. power	W	630*
Cooling power	W	615**
Input voltage		1x230V ~ 50Hz
Energy efficiency class		D
Energy consumption kWh/24h	kWh/24h	5,36
Energy consumption kWh/year	kWh/year	1957
Energy efficiency index		54,3
Climate class		5
Packaging dimensions (WxDxH)	cm	77 x 96 x 224
Volume (gross)	mc	1,66
Net weight	kg	139
Gross weight	kg	149

Evap. -10°C, cond. +45°C/*ASHRAE (evap. -23,3 cond. +54,4°C)


DETAILS:



Internal details of deep-drawn stainless steel-sides



Ventilated cooling system



Door lock with key and internal light




Ecological gas (R290)

Remote monitoring system via GEMM-Cloud Wi-Fi connection (on request)

ACCESSORIES:


	GN 2/1 shelf	45000500
	GN 2/1 stainless steel shelf	45000515
	Pedal for single door	45000530
	Set of Ø 100 castors	45000540
	Wi-Fi supervising system (overprice)	45000565
	60Hz frequency	40200560
	Prearranged version with valve system for low temperature equipment (deduction)	

INSTALLATION DIAGRAM:



XFB/71

ECOLABEL:


ENERG
енергия · ενεργεια
Y
IJA
IE
IA
GEMM srl
XFB/71 NEW
A+++
A++
A+
A
B
C
D
E
F
G
D
ENERGIA · ЕНЕРГИЯ · ΕΝΕΡΓΕΙΑ
ENERGIJA · ENERGY · ENERGIE
ENERGI
1957
kWh/annum
1L
- L
433 L
5
40°C-40%
2015/1094-IV