

PROFESSIONAL KITCHENS

CABINETS FOR PROFESSIONAL KITCHENS

Model: XFBV/70


Code: 45002135

SPACE PLUS

GN 2/1 NEGATIVE UPRIGHT CABINET WITH GLASS DOOR - Freezer upright cabinet glass door for GN 2/1 racks, complete with led light. Prearranged for remote condensing unit with valve system on request.

- Construction: made in stainless steel
- Deep-drawn internal sides
- Internal capacity: GN 2/1 racks
- Position of technical compartment: on top
- Refrigeration type: ventilated cooling system
- Control board panel: 2.8" touch control panel, digital display
- Prearranged to be installed on plinth
- Defrosting system: automatic with hot gas
- Evaporation of condensation water: automatic
- Optional equipment: prearranged for remote system (R452A gas valve)
- Supply with: 3 GN 2/1 shelves





Technical Data:

Doors	nr	1
Capacity (net)	l	433
Capacity (gross)	l	556
External dimensions (WxDxH)	cm	70 x 87 x 209
Insulation thickness	mm	80
Tray pitch	mm	55
Rack positions	nr	24
Standard lock		YES
Standard light		YES
Temperature	°C	-18/-21°C
Condensing unit		plug-in unit
Compressor power	Hp	1/2
Gas		R290
Ventilation control		NO
Humidity control		NO
Max abs. power	W	615*
Cooling power	W	615**
Input voltage		1x230V ~ 50Hz
Energy efficiency class		E
Energy consumption kWh/24h	kWh/24h	7,48
Energy consumption kWh/year	kWh/year	2728
Energy efficiency index		75,5
Climate class		4
Packaging dimensions (WxDxH)	cm	77 x 96 x 224
Volume (gross)	mc	1,66
Net weight	kg	147
Gross weight	kg	157

Evap. -10°C, cond. +45°C/ASHRAE (evap. -23,3 cond. +54,4°C)

DETAILS:



Internal details of deep-drawn stainless steel-sides



Ventilated cooling system



Door lock with key and internal light



Digital touch thermostat



Ecological gas (R290)



Remote monitoring system via GEMM-Cloud Wi-Fi connection (on request)

ACCESSORIES:



GN 2/1 shelf

45000500



GN 2/1 stainless steel shelf

45000515



Pedal for single door

45000530



Set of Ø 100 castors

45000540



Wi-Fi supervising system (overprice)

45000565



60Hz frequency

40200560

INSTALLATION DIAGRAM:

NOTE
REV.01 18/03/2025

705 0257 00

CODICE

NOME FILE

DESCRIZIONE
**SCHEMA INSTALLAZIONE
XFNV-XFBV 70 NEW R290**

DATA
30/09/2024

SCALA
1:20

DIS.
DIS.

- AI TERMINI DI LEGGE QUESTO DISEGNO E' DI NOSTRA PROPRIETA' E NON PUO' ESSERE USATO O RIPRODOTTO SENZA NOSTRA AUTORIZZAZIONE -

GAS REFRIGERANTE R290 / R290 REFRIGERANT GAS

ALIMENTAZIONE ELETTRICA / ELECTRICITY SUPPLY: 230V 50HZ (*spina SCHUKO/ SCHUKO plug)

Lunghhezza cavo 3mt / 3mt wire length

POTENZA ELETTRICA MAX ASSORBITA / MAX ABSORBED ELECTRIC POWER (TN) : 185 W

POTENZA ELETTRICA MAX ASSORBITA / MAX ABSORBED ELECTRIC POWER (BT) : 630 W

POTENZA REFRIGERANTE / COOLING POWER TN (-10°C+45°C): 425 W

POTENZA REFRIGERANTE / COOLING POWER BT (-23,3°C+54,4°C): 655W

XFBV/70

ECOLABEL:

