

## PASTRY|PIZZERIA

### PASTRY CABINETS

Model: ARP/20B


Code: 45010505

#### *DELICE*

PASTRY NEGATIVE UPRIGHT CABINET 20 TRAYS - Pastry freezer cabinet for 20 600x400 trays. Available also prearranged for remote condensing unit with valve system.

- Construction: made in stainless steel
- "Overcooling" and "energy saving" functions
- Internal capacity: 20 600x400 mm trays
- Position of technical compartment: on top
- Refrigeration type: "Gentle" cooling system with indirect/soft ventilation
- Control board panel: 2.8" touch control panel, digital display
- Prearranged to be installed on plinth
- Defrosting system: automatic with hot gas
- Evaporation of condensation water: automatic
- 74 positions for shelves
- Optional equipment: prearranged for remote system (R452A gas valve)
- Supply with: 20 pair of runners for 600x400 trays





## Technical Data:

Doors	nr	1
Capacity (net)	l	304
Capacity (gross)	l	500
Capacity of trays/shelves	mm	20
External dimensions (WxDxH)	cm	79 x 69 x 214
Insulation thickness	mm	75
Tray pitch	mm	16,5
Rack positions	nr	74
Standard lock		NO
Standard light		NO
Temperature	°C	-22/-10°C
Condensing unit		plug-in unit
Gas		R290
Ventilation control		NO
Humidity control		NO
Max abs. power	W	795*
Cooling power	W	650**
Input voltage		1x230V ~ 50Hz
Energy efficiency class		D
Energy consumption kWh/24h	kWh/24h	5,52
Energy consumption kWh/year	kWh/year	2016
Energy efficiency index		67,9
Climate class		5
Packaging dimensions (WxDxH)	cm	87 x 77 x 226
Volume (gross)	mc	1,51
Net weight	kg	138
Gross weight	kg	148

\*Evap. -10°C, cond. +45°C/\*\* ASHRAE (evap. -23,3 cond. +54,4°C)

## DETAILS:



Internal cell probe for constant temperature monitoring



Evaporators with cataphoresis treatment and electronic fans



Constant temperature monitoring with digital control board



Custom color finish available on request



Racks with easily removable guides featuring 74 positions (16.5 mm pitch)



Ecological gas (R290)



Remote monitoring system via GEMM-Cloud Wi-Fi connection (on request)

## ACCESSORIES:



Pair of runners for cm 60x40 tray

45020503



Rilsan cm 60x40 shelf

45020550



Stainless steel cm 60x40 shelf

45100242



Stainless steel cm 40x60x2h tray

42000560

Stainless steel cm 40x60x3h tray

42000562



Toughened glass door with internal LED light (overprice)

45020525



Cabinet LED light

45020530



Set of Ø 100 castors

45000540



Wi-Fi supervising system (overprice)

45000565



60Hz frequency

40200560



Prearranged version with valve system for low temperature equipment (deduction)

## INSTALLATION DIAGRAM:

GAS REFRIGERANTE R290  
 R290 REFRIGERANT GAS  
 ALIMENTAZIONE ELETTRICA / ELECTRICAL SUPPLY: 230V 50HZ (\*spina  
 SCHUKO / SHUKO plug) Lunghezza cavo 3mt / 3mt Wire length

POTENZA ELETTRICA MAX ASSORBITA / MAX ABSORBED ELECTRIC  
 POWER (TN) : 500 W POTENZA ELETTRICA MAX ASSORBITA/ MAX  
 ABSORBED ELECTRIC POWER (BT) : 795 W

POTENZA REFRIGERANTE / COOLING POWER TN (-10/°C+45°C): 605 W  
 POTENZA REFRIGERANTE / COOLING POWER BT (-23,3/°C+54,4°C): 650 W

NOTE  
REV.1 03/04/2025

705 0326 00

CODICE

NOME FILE

DESCRIZIONE  
**SCHEMA INSTALLAZIONE  
ARM. ARP/20 - ARP/20B**

DIS. A PAVAN

DATA 10/05/2022

SCALA 1:20

- AI TERMINI DI LEGGE QUESTO DISEGNO E' DI NOSTRA PROPRIETA' E NON PUO' ESSERE USATO O RIPRODOTTO SENZA NOSTRA AUTORIZZAZIONE -

ARP/20B

ECOLABEL:

