

PASTRY|PIZZERIA

PASTRY CABINETS

Model: ARP/41B


Code: 45010525

DELICE

PASTRY NEGATIVE UPRIGHT CABINET 40 TRAYS, 2 HALF DOORS - Pastry freezer cabinet for 40 600x400 trays. Available also prearranged for remote condensing unit with valve system.

- Construction: made in stainless steel
- "Overcooling" and "energy saving" functions
- Internal capacity: 40 600x400 mm trays
- Position of technical compartment: on top
- Refrigeration type: "Gentle" cooling system with indirect/soft ventilation
- Control board panel: 2.8" touch control panel, digital display
- Prearranged to be installed on plinth
- Defrosting system: automatic with hot gas
- Evaporation of condensation water: automatic
- 74 positions for shelves
- Optional equipment: prearranged for remote system (R452A gas valve)
- Supply with: 20 pair of runners for 600x800 trays





Technical Data:

Doors	nr	1
Capacity (net)	l	608
Capacity (gross)	l	900
Capacity of trays/shelves	mm	40
External dimensions (WxDxH)	cm	79 x 108 x 214
Insulation thickness	mm	75
Tray pitch	mm	16,5
Rack positions	nr	74
Standard lock		NO
Standard light		NO
Temperature	°C	-22/-10°C
Condensing unit		plug-in unit
Gas		R290
Ventilation control		NO
Humidity control		NO
Max abs. power	W	1200*
Cooling power	W	920**
Input voltage		1x230V ~ 50Hz
Energy efficiency class		D
Energy consumption kWh/24h	kWh/24h	8,66
Energy consumption kWh/year	kWh/year	3162
Energy efficiency index		70,7
Climate class		5
Packaging dimensions (WxDxH)	cm	87 x 114 x 226
Volume (gross)	mc	2,24
Net weight	kg	195
Gross weight	kg	205

*Evap. -10°C, Cond. +45°C / **Evap. -23,3 Cond. +54,4°C

DETAILS:



Internal cell probe for constant temperature monitoring



Evaporators with cataphoresis treatment and electronic fans



Constant temperature monitoring with digital control board



Custom color finish available on request



Racks with easily removable guides featuring 74 positions (16.5 mm pitch)



Ecological gas (R290)



Remote monitoring system via GEMM-Cloud Wi-Fi connection (on request)

ACCESSORIES:



Pair of runners for cm 60x80 shelf

45020511

Rilsan cm 60x80 shelf

45020512

Stainless steel 60x80 cm shelf

45020515



Stainless steel cm 40x60x2h tray

42000560

Stainless steel cm 40x60x3h tray

42000562



Stainless steel cm 60x80x2h tray

45020520



Toughened glass door with internal LED light (overprice)

45020525



Cabinet LED light

45020530



Set of Ø 100 castors

45000540



Wi-Fi supervising system (overprice)

45000565



60Hz frequency

40200560



Prearranged version with valve system for low temperature equipment (deduction)

INSTALLATION DIAGRAM:

GAS REFRIGERANTE R290 / R290 REFRIGERANT GAS
ALIMENTAZIONE ELETTRICA ELECTRICAL SUPPLY: 230V 50HZ (*spina SCHUKO / SHUKO plug)
 Lunghezza cavo 3mt / 3mt wire length

⚡ **POTENZA ELETTRICA MAX ASSORBITA / MAX ABSORBED ELECTRICAL POWER (TN) : 715 W**
 ⚡ **POTENZA ELETTRICA MAX ASSORBITA / MAX ABSORBED ELECTRICAL POWER (BT) : 1200 W**
POTENZA REFRIGERANTE / COOLING POWER TN (-10°C+45°C): 1005 W
REFRIGERANTE / COOLING POWER BT (-23,3°C+54,4°C): 920 W

DESCRIZIONE		SCHEMA INSTALLAZIONE		CODICE		NOTE	
ARM. ARP/41 - ARP/41B		DIS. M. MICHELE		705 0301 00		REV.1 09/04/2025	
DATA	29/07/2021	SCALA	1:20	NOME FILE			
- AI TERMINI DI LEGGE QUESTO DISEGNO E' DI NOSTRA PROPRIETA' E NON PUO' ESSERE USATO O RIPRODOTTO SENZA NOSTRA AUTORIZZAZIONE -							

ARP/41B

ECOLABEL:

