

PASTRY

PASTRY CABINETS

Model: ADPV/40C


Code: 45011135

DELICE PLUS

CHOCOLATE UPRIGHT CABINET WITH 45-65% HUMIDITY CONTROL, 40 TRAYS, WITH GLASS DOOR - Chocolate refrigerated cabinet for 40 600x400 trays. Electronic humidity probe for humidity control. Available also prearranged for remote condensing unit with valve system.

- Construction: made in stainless steel
- "Overcooling", "energy saving" and "extra humidity" functions
- Internal capacity: 40 600x400 mm trays
- Position of technical compartment: on top
- Refrigeration type: "Gentle" cooling system with indirect/soft ventilation
- Control board panel: 2.8" LCD digital touch control
- Prearranged to be installed on plinth
- Defrosting system: automatic with hot gas
- Evaporation of condensation water: automatic
- 74 positions for shelves
- Optional equipment: prearranged for remote system (R452A gas valve)
- Supply with: 20 pair of runners for 600x800 trays





Technical Data:

Doors	nr	1
Capacity (net)	l	608
Capacity (gross)	l	900
Capacity of trays/shelves	mm	40
External dimensions (WxDxH)	cm	79 x 108 x 214
Insulation thickness	mm	75
Tray pitch	mm	16,5
Rack positions	nr	74
Standard lock		NO
Standard light		YES
Temperature	°C	+4/+18°C
Condensing unit		plug-in unit
Gas		R290
Ventilation control		NO
Humidity control		YES
Relative humidity	ur%	45-65%
Max abs. power	W	1870*
Cooling power	W	1005*
Input voltage		1x230V ~ 50Hz
Climate class		4
Packaging dimensions (WxDxH)	cm	87 x 114 x 226
Volume (gross)	mc	2,24
Net weight	kg	193
Gross weight	kg	203

*Evap. -10°C, Cond +45°C

DETAILS:



Custom color finish available on request



Racks with easily removable guides featuring 74 positions (16.5 mm pitch)



Control electronic board for the constant management of temperature and relative humidity



Electronic probe for relative humidity detection



Ecological gas (R290)



Remote monitoring system via GEMM-Cloud Wi-Fi connection (on request)

ACCESSORIES:



Pair of runners for cm 60x80 shelf

45020511

Rilsan cm 60x80 shelf

45020512

Stainless steel 60x80 cm shelf

45020515



Stainless steel cm 40x60x2h tray

42000560

Stainless steel cm 40x60x3h tray

42000562



Stainless steel cm 60x80x2h tray

45020520



Set of Ø 100 castors

45000540



Wi-Fi supervising system (overprice)

45000565



60Hz frequency

40200560

INSTALLATION DIAGRAM:

DESCRIZIONE		SCHEMA INSTALLAZIONE		NOTE	
ARM. ADPV/40 - ADPV/40C		CODICE		705 0430 00	
DATA	03/04/2025	SCALA	1:20	DIS.	L.P.
- A TERMINI DI LEGGE QUESTO DISEGNO E' DI NOSTRA PROPRIETA' E NON PUO' ESSERE USATO O RIPRODOTTO SENZA NOSTRA AUTORIZZAZIONE -					

GAS REFRIGERANTE R290
 R290 REFRIGERANT GAS
 ALIMENTAZIONE ELETTRICA / ELECTRICITY SUPPLY: 230V 50HZ (*spina SCHUKO / SCHUKO plug) Lunghezza cavo 3mt / 3mt wire length
 POTENZA ELETTRICA MAX ASSORBITA / MAX ABSORBED ELECTRIC POWER: 1870 W
 POTENZA REFRIGERANTE / COOLING POWER (-10°C+45°C): 1005 W

ADPV/40C