

RETARDER PROOFING

RETARDER-PROOFING CABINETS

Model: AFLV/20


Code: 45020300

PLANET

RETARDER PROVER CABINET 20 TRAYS - Retarder-prover cabinet for 20 600x400 trays, electronic humidity probe for humidity control.

- Construction: made in stainless steel
- Multifunction and multilingual
- Internal capacity: 20 600x400 mm trays
- Position of technical compartment: on top
- Refrigeration type: "Gentle" cooling system with indirect/soft ventilation
- Control board panel: 5" TOUCH screen control board
- Backing delay function
- Defrosting system: automatic with heating elements
- Evaporation of condensation water: automatic
- Supply with: 20 pair of runners for 600x400 trays





Technical Data:

Doors	nr	1
Capacity (net)	l	304
Capacity (gross)	l	500
Capacity of trays/shelves	mm	20 600x400
External dimensions (WxDxH)	cm	79 x 69 x 214
Insulation thickness	mm	75
Tray pitch	mm	16,5
Rack positions	nr	74
Evaporators	nr	1
Standard lock		NO
Standard light		NO
Temperature	°C	-10/+35°C
Condensing unit		plug-in unit
Gas		R290
Ventilation control		NO
Humidity control		NO
Relative humidity	ur%	60-90%
Max abs. power	W	1250***
Cooling power	W	675*
Input voltage		1x230V ~ 50Hz
Climate class		5
Packaging dimensions (WxDxH)	cm	87 x 77 x 226
Volume (gross)	mc	1,51
Net weight	kg	164
Gross weight	kg	174

*Evap. -10°C, Cond +45°C / *** Heating

DETAILS:



Humidity control with electronic probe



"Full control" electronic fans



"Gentle" refrigeration: Perforated back for indirect airflow



Racks with easily removable runners with 74 positions (16.5 mm pitch)



Ecological gas (R290)



USB port for data uploads and downloads useful for recipes, parameters and HACCP datas



5" TOUCH electronic board



Automatic work cycle



Manual work cycle



Remote monitoring system via GEMM-Cloud Wi-Fi connection (on request)

ACCESSORIES:



Pair of runners for cm 60x40 tray

45020503



Rilsan cm 60x40 shelf

45020550



Stainless steel cm 60x40 shelf

45100242



Stainless steel cm 40x60x2h tray

42000560

Stainless steel cm 40x60x3h tray

42000562



Toughened glass door with internal LED light (overprice)

45020525



Set of Ø 100 castors

45000540



Wi-Fi supervising system for AFLV, BCT (overprice)


45000563



60Hz frequency

40200560

INSTALLATION DIAGRAM:



AFLV/20