

## ICE CREAM|PASTRY|PROFESSIONAL KITCHENS

BLAST CHILLERS/SHOCK FREEZERS FOR TROLLEYS

Model: GT4/0580

Code: 45101100

## NEW RUNNER

TUNNEL BLAST CHILLER / SHOCK FREEZER FOR 5 GN 2/1 - 600X800 TROLLEYS - Blast freezer which gets rapidly lower the core temperature of foods: chilling from +90°C to +3°C in 90 minutes and freezing from +90°C to -18°C in 240 minutes. Equipped with multifunction and multilingual electronic board that allows, thanks to the 7" color touch-screen graphic display, to easily organize the working cycles, to set multiple functions and to have a complete controle on the blast chilling or freezing. The board is connected to the Wi-Fi device, via Cloud platform, to supervise and modify the operation of the equipment or to diagnose any problems remotely (PC, tablet or smartphone).

· Construction: made in stainelss steel

- reinforced floor with stainless steel cover and stainless steel ramp
- core probe, USB door, GEMM-Cloud as standard
- Internal capacity: no. 5 GN 2/1 or 600x800 trolleys
- Position of technical compartment: on top

• Refrigeration type: chilling from +90°C to +3°C in 90 minutes and freezing from +90°C to -18°C in 240 minutes, reaching minimum air temperature -40°C

- Control board panel: 7" TOUCH screen control board
- special cycles: continuous cycle, fish sanitizing cycle, prechilling, drying cycle. Recipe book
- Defrosting system: automatic defrosing system with hot gas
- Evaporation of condensation water: condensation drain pipe (prearrange water drain)
- Machine supplied not assembled
- Not included: trolleys





## Technical Data:

| Davie                       |    |                        |
|-----------------------------|----|------------------------|
| Doors                       | nr | 2                      |
| Trolley capacity            | nr | 5 GN 2/1/60x80         |
| External dimensions (WxDxH) | cm | 160 x 425 x 243        |
| Insulation thickness        | mm | 100                    |
| Internal dimensions (WxDxH) | cm | 90 x 374 x 200         |
| Standard lock               |    | YES                    |
| Standard light              |    | YES                    |
|                             |    | +90/+3°C = Kg 820      |
| Yield* chilling / freezing  | kg | +90/-18°C = Kg 750     |
| Condensing unit             |    | remote condensing unit |
| Compressor power            | Нр | 18,0 + 18,0            |
| Ventilation control         |    | YES                    |
| Humidity control            |    | NO                     |
| Max abs. power              | W  | 2910 / 37320*          |
| Cooling power               | W  | 34520**                |
| Input voltage               |    | 3x400V ~ 50Hz          |
| Climate class               |    | 5                      |

\*Evap. -10°C, Cond. +45°C / \*\*Evap. -23,3 Cond. +54,4°C \*\*\*Ambient temp. +30°C loading sample according to EN 17032:2018

## ACCESSORIES:

| ₩.ee | Winter kit for remote condensing unit BCC/8027P GT2/ GT3/ GT4/ GT5/ (overprice) | 45100919 |
|------|---|----------|
| ų    | 60Hz frequency  | 40200560 |