

ICE CREAM|PASTRY|PROFESSIONAL KITCHENS

BLAST CHILLERS/SHOCK FREEZERS FOR TROLLEYS

Model: GT5/0698

Code: 45101150

NEW RUNNER

TUNNEL BLAST CHILLER / SHOCK FREEZER FOR 6 GN 2/1 - 600X800 TROLLEYS - Blast freezer which gets rapidly lower the core temperature of foods: chilling from +90°C to +3°C in 90 minutes and freezing from +90°C to -18°C in 240 minutes. Equipped with multifunction and multilingual electronic board that allows, thanks to the 7" color touch-screen graphic display, to easily organize the working cycles, to set multiple functions and to have a complete controle on the blast chilling or freezing. The board is connected to the Wi-Fi device, via Cloud platform, to supervise and modify the operation of the equipment or to diagnose any problems remotely (PC, tablet or smartphone).



- Construction: made in stainless steel
- reinforced floor with stainless steel cover and stainless steel ramp
- core probe, USB door, GEMM-Cloud as standard
- Internal capacity: no. 6 GN 2/1 or 600x800 trolleys
- Position of technical compartment: on top
- Refrigeration type: chilling from +90°C to +3°C in 90 minutes and freezing from +90°C to -18°C in 240 minutes, reaching minimum air temperature -40°C
- Control board panel: 7" TOUCH screen control board
- special cycles: continuous cycle, fish sanitizing cycle, pre-chilling, drying cycle. Recipe book
- Defrosting system: automatic defrosting system with hot gas
- Evaporation of condensation water: condensation drain pipe (prearrange water drain)
- Machine supplied not assembled
- Not included: trolleys



Technical Data:

Doors	nr	2
Trolley capacity	nr	6 GN 2/1/60x80
External dimensions (WxDxH)	cm	160 x 517 x 243
Insulation thickness	mm	100
Internal dimensions (WxDxH)	cm	90 x 466 x 200
Standard lock		YES
Standard light		YES
Yield* chilling / freezing	kg	+90/+3°C = Kg 980 +90/-18°C = Kg 920
Condensing unit		remote condensing unit
Compressor power	Hp	18,0 + 27,0
Ventilation control		YES
Humidity control		NO
Max abs. power	W	3595 / 45140*
Cooling power	W	41760**
Input voltage		3x400V ~ 50Hz
Climate class		5

*Evap. -10°C, Cond. +45°C / **Evap. -23,3 Cond. +54,4°C

Ambient temp. +30°C loading sample according to EN 17032:2018

ACCESSORIES:



Winter kit for remote condensing unit BCC/8027P GT2/ GT3/ GT4/ GT5/
(overprice)

45100919



60Hz frequency

40200560